

American Standard

FFAS1772-701GL0BT0



Technical drawing of a shower system (model 1000-1250) showing front, side, and top views with dimensions.

Front View (Left): Shows the shower head (Ø 110) and the control handle. The distance from the shower head to the handle is 1300 ± 15. The distance from the handle to the base is 150 ± 15.

Side View (Right): Shows the shower head and the control handle. The distance from the shower head to the handle is 1300 ± 150. The distance from the handle to the base is 178.

Top View (Bottom): Shows the base of the shower system. The distance from the center of the base to the edge is 250. The distance from the center of the base to the edge of the shower head is 250. The distance from the center of the base to the edge of the shower head is 250.

- A grade brass, strong and durable
- Grohe High quality ceramic valve for longer usage
- Ceramic cartridge tested = 500,000 times
- With Ceramic 3-way diverter cartridge
- With Rainshower kit
- With 3F hand shower
- With Easy-slide shower holder
- With 1.5m Twist-free shower hose
- With normal packaging
- Flow rate @ 0.1MPa: 7.5 L/min for Spout
- Flow rate @ 0.1MPa: 5.1 L/min for shower head
- Flow rate @ 0.1MPa: 4.6 L/min for hand shower

- Exposed Bath & Shower Mixer Faucet
- 2-Hole Installation: lever handle (cold & hot)

PVD Polished Cool Sunrise

- N/A

- Product gross weight: 8.0kg /set
- Product net weight: 5.93kg /set

■ GB 18145-2014
TIS2066-2552