

Finished wall

60mm

Recommended faucet position

Outer line of lavatory

155mm

Cutting line

380mm

Square thin 500mm UC CP-F514

Installation template

Remark: The installation instruction is supplied for export products only!

AMERICAN STANDARD LIMITED WARRANTY

If inspection of these AMERICAN STANDARD products, within a period of warranty after purchasing, confirms that its defective under normal use in material or workmanship, AMERICAN STANDARD will repair or, at its option exchange the product of a similar model.

The warranty does not cover the following:

1. None any documentary evidenced to show the period of warranty such as receipt, warranty card, etc.
2. Consequential or incidental damages.
3. Defects or damages arising from shipping, installation, alteration, accidents, misuse or lack of proper maintenance.
4. Postage or shipping costs included in returning products for repair or replacement under this warranty and any labor or other costs of removal or installation of products under this warranty.
5. A product discontinued.

INSTALLATION

1. Preparation of the area for installation.
2. Place the template on the counter with position required.
3. Cut the counter following the cutting line on the template
4. Install fittings and drain assembly, per instructions supplied by manufacturer.
5. Apply sealing silicone to the basin rim, place the basin to installing position.
Then install with the bracket.
6. Remove the excess silicone after installation.
7. Connect water supply and check the leakage.

Lava

500mm